



# FALK®

## NORTH AMERICAN PERFORMANCE RATING & TESTING

TEST	METHOD	DESCRIPTION	RESULTS
<b>FIRE</b>			
	ASTM E84 - 21	Standard Method of Test for Surface Burning Characteristics of Building Materials <i>(The foregoing test procedure is comparable to UL 723, ANSI/NFPA No. 255, and UBC No. 8- 1)</i>	PASS  When Tested in Accordance to ASTM E84-21 the Material Resulted in a Class 'A'  Flame Spread: 25 Smoke Developed: 75
	ASTM E84 - 18b	Standard Method of Test for Surface Burning Characteristics of Building Materials <i>(The foregoing test procedure is comparable to UL 723, ANSI/NFPA No. 255, and UBC No. 8- 1)</i>	PASS  When Tested in Accordance to ASTM E84-21, the Material Resulted in a Class 'A'  Flame Spread: 20 Smoke Developed: 300
	UL 1256 Part II - 4th	Describes a Test Which Appraises Fire Performance of Non-Metallic and Metallic Roof Deck Constructions Subjected to an Internal (Under Deck) Fire Exposure.	Flame Spread: < 10 feet in 10 minutes  Flame Spread: <14 feet in 30 minutes  No Thermal Degradation Through All Components of Roof Deck Assembly  Decreasing Thermal Degradation With Increased Distance From Burner  3.7 Pass  7.3 Pass  Met Pass  Met Pass
	ASTM D1929-20	Standard Test Method for Determining Ignition Temperature of Plastics	PASS  Flash-Ignition: 387°C 730°F  Self-Ignition: 429°C 805°
	CAN/ULC-S127	Standard Corner Wall Method of Test for Flammability Characteristics of Non-Melting Foam Plastic Building Materials	PASS  Flame Spread: <500 for foam core
	CAN/ULC-S101-14	National Building Code of Canada 2015 (NBC), Article 3.1.5.7. Factory Assembled Panels clause (2) item b) iii) referencing the CAN/ULC S101-14 10 Minute Remain in Place.	Meets Requirements
	CAN/ULC-S102-10	Standard Method of Test for Surface Burning Characteristics of Building Materials and Assemblies	PASS  Flame Spread: 20 Smoke Developed: 190
	CAN/ULC-S138-06	Fire Growth of Insulated Building Panels in a Full-Scale	Meets Requirements
	CAN/ULC-S126	Evaluation of Fire Spread Under Roof-Deck Assemblies	Meets Requirements
	NFPA 286	Evaluating Contribution of Wall and Ceiling Interior Finish to Room Fire	Meets Requirements
	NFPA 285	Evaluation of Fire Propagation Characteristics of Exterior Wall Assemblies Containing Combustible Components	Pass



MANUFACTURING & US SALES:

1782 Northridge Dr NW, Walker MI 49544  
616.541.4500

www.falk.com

CANADA SALES:

11 Fulton Road, Rocky View County, AB, T1X 0Z1  
587 349 1777



# FALK®

## NORTH AMERICAN PERFORMANCE RATING & TESTING

TEST	METHOD	DESCRIPTION	RESULTS
<b>STRUCTURAL</b>			
	ASTM E455, E72 and AISI S907	Shear Load Tests on Roof and Wall Panels	See Span and Load Tables
	ASTM E1592	Gravity and Uplift Load Tests on Roof Panels	See Span and Load Tables
	ANSI FM 4474	Standard for Evaluating the Simulated Wind Uplift Resistance of Roof Assemblies	Contact FALK Customer Service
<b>THERMAL</b>			
	ASTM C518-21	Standard Test Method for Steady-State Thermal Transmission Properties by Means of the Heat Meter Apparatus	(R) 7.5 R-VALUE [H.FT <sup>2</sup> ·°F/BTU]
<b>AIR</b>			
	ASTM E283/ E283M-19	Standard Test Method for Determining Rate of Air Leakage Through Exterior Windows, Skylights, Curtain Walls, and Doors Under Specified Pressure Differences Across the Specimen	<0.1 L/s/m <sup>2</sup> (<0.01 cfm/ft <sup>2</sup> )
	ASTM 1680-16	Standard Test Method for Rate of Air Leakage through Exterior Metal Roof Panel Systems	<0.01 cfm/ft <sup>2</sup> (0.1 L/s/m <sup>2</sup> )
<b>WATER</b>			
	ASTM E331-00(2016)	Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Uniform Static Air Pressure Difference	580 Pa (12.11 psf)
	ASTM E1646-95	Standard Test Method for Water Penetration of Exterior Metal Roof Panel Systems by Uniform Static Air Pressure Difference Leakage through Exterior Metal Roof Panel Systems	12.0 psf (575 Pa) Pass 20.0 psf (958 Pa) Pass
<b>SPECIAL</b>			
	Florida Building Code	Florida Certificate of Product Approval # FL41818 - Structural Wall	Meets Requirements
		Florida Certificate of Product Approval # FL41819 - Structural Roof	Meets Requirements
	Texas Department of Insurance	TDI Approval TP-0877	Meets Requirements
	QAI	Building Product Listing Program Listing # B1142-1	See Listing for Details
	Environmental Product Declaration	SCS-EPD-10288 EPD Valid 11-8-2024 through 11-7-2029	See EPD for Details



MANUFACTURING & US SALES:

1782 Northridge Dr NW, Walker MI 49544  
616.541.4500

| [www.falk.com](http://www.falk.com) |

CANADA SALES:

11 Fulton Road, Rocky View County, AB, T1X 0Z1  
587 349 1777

## FM APPROVALS

PRODUCT	WIDTH	CORE THICKNESS	APPROVAL STANDARD				SPECIFICATIONS
			4880	4881	4470	4471	
Hidden Fixed Wall Panel (HFW)	40"	2.5" - 6"	✓	✓			5' purlin spacing with 14 gauge purlin +/- 45 psf Zone Tropical Cyclone
Cold Storage Wall Panel (CSW)	44"	2.5" - 8"	✓				Class A - Unlimited height
Standing Seam Roof Panel (SSR)	42"	3" - 6"	✓			✓	RoofNav #568917 5' purlin spacing with 14 gauge purlin Wind Uplift Rating: 1-105 psf Internal Fire Rating: Class 1 External Fire Rating: Class A Hail Rating: Severe Hail Slope Rating: 5:12
Ribbed Roof Panel (RRP)	40"	2.5" - 6"	✓			✓	RoofNav #568918 5' purlin spacing with 16 gauge purlin Wind Uplift Rating: 1-105 psf Internal Fire Rating: Class 1 External Fire Rating: Class A Hail Rating: Severe Hail Slope Rating: 5:12
RDEK Panel	40"	2.5"-6"	✓		✓	✓	RoofNav #568919 & #568920 5' purlin spacing with 16 gauge purlin Wind Uplift Rating: 1-105 & 1-120 psf Internal Fire Rating: Class 1 External Fire Rating: Class A Hail Rating: Severe Hail Slope Rating: 0.5:12 & 1.5:12

Contact FALK Customer Service for more details.